



## Blue Logic 17H Dual Port (Type B)

### High pressure hydraulic hot stab

The Blue Logic 17H dual port conforms to ISO 13628-8, but has larger internal fluid paths and integral sealing valves. The male has four check valves set inside the male body therefore will not dump the ROV compensator pressure. These minimise ROV oil leakage and water ingress, and prevent underpressure in the hoses, etc.

The female receptacle has two screw-in cartridges that do the same, but are normally 0.2bar in/out. The female can be mounted by U-bolts around the body or flange; mounted by four bolts using a top-mounting interface plate.

#### Applications

Subsea QD operations

#### Features

- Industry standard
- ISO 13628-8 Type B
- Up to 70lpm / 18.5gpm
- 345bar / 5,000psi
- Integral sealing valves
- Pressure balanced

#### In the box

- Blue Logic 17H dual port (Type B)
- Operational hoses
- Operations and maintenance manual



# Blue Logic 17H Dual Port (Type B)

## Specifications

Working pressure	345bar / 5,000psi
Flow rate	70lpm / 18.5gpm
Hydraulic fluid and gases	345bar / 5,000psi
Weight	4.7kg / 10.3lbs
Port sizes	All ports 3/8" BSP
Flow path	11mm / 0.43in
Materials	UNSC63200

