



## 10,000psi 17H Single Port (Type B)

### High pressure hydraulic hot stab

The single port conforms to ISO 13628-8, but has larger internal fluid paths and integral sealing valves. The male has four check valves set inside the male body.

These are 0.2bar inflow, 2.5bar outflow (i.e., will not dump the ROV compensator pressure). These minimise ROV oil leakage and water ingress, and prevent underpressure in the hoses, etc.

The female receptacle has two screw-in cartridges that do the same, but are normally 0.2bar in/out. The female can be mounted by U-bolts around the body or flange; mounted by four bolts using a top-mounting interface plate.

Note: Flows up to 40lpm can be achieved, check valves are only rated to 30lpm so need to be removed from system to achieve high flow.

#### Applications

Subsea QD operations  
Chemical & gas injection  
Flooding & venting operations

#### Features

Industry standard  
ISO 13628-8 Type B  
Up to 30lpm / 7.9gpm  
690bar / 10,000psi  
Integral sealing valves  
Pressure balanced

#### In the box

10,000psi 17H single port (Type B)  
Operational hoses  
Operations and maintenance manual



# 10,000psi 17H Single Port (Type B)

## Specifications



Working pressure	690bar / 10,000psi
Flow rate	30lpm / 7.92gpm
Hydraulic fluid and gases	690bar / 10,000psi
Weight	4.4kg / 9.7lbs
Port sizes	All ports 3/8" NPT
Flow path	8mm / 0.3in
Materials	Stainless steel UNS S31803

**Aberdeen**  
+44 (0)1224 771888

**Abu Dhabi**  
+971 2 650 7710

**Houston**  
+1 281 398 9533

**Singapore**  
+65 6545 9350