



## 3,000psi 17H Dual Port (Type A)

### Low pressure hydraulic hot stab

The dual port conforms to ISO 13628-8, but has larger internal fluid paths and integral sealing valves. The male has four check valves set inside the male body.

These are 0.2bar inflow, 2.5bar outflow (i.e., will not dump the ROV compensator pressure). These minimise ROV oil leakage and water ingress, and prevent underpressure in the hoses, etc.

The female receptacle has two screw-in cartridges that do the same, but are normally 0.2bar in/out. The female can be mounted by U-bolts around the body or flange; mounted by four bolts using a top-mounting interface plate.

Note: Flows up to 40lpm can be achieved, check valves are only rated to 30lpm so need to be removed from system to achieve high flow.



#### Applications

Subsea QD operations  
Chemical & gas injection  
Flooding & venting operations

#### Features

Industry standard  
ISO 13628-8 Type A  
Up to 30lpm / 7.92gpm  
207bar / 3,000psi  
Integral sealing valves  
Pressure balanced

#### In the box

3,000psi 17H dual port (Type A)  
Operational hoses  
Operations and maintenance manual

# 3,000psi 17H Dual Port (Type A)

## Specifications

Working pressure	207bar / 3,000psi
Flow rate	30lpm / 7.92gpm
Hydraulic fluids and gases	207bar / 3000psi
Weight	4kg / 8.8lbs
Port sizes	All ports 3/8" NPT
Flow path	8mm / 0.3in
Materials	Stainless steel 316L and duplex

