

VARIOUS RESCUE TOOLS

concrete crusher		CC 23	
art. no.		150.012.295	
max. opening	mm	230	
max. crushing force	kN / t	113 / 11.5	
shape of tip		pointed	
weight ready for use	kg	19.1	

- Heavy-duty: designed to quickly break away large, thick pieces of concrete
- Limited dust: supports a clear view at the rescue scene
- No vibrations: prevents risk of secondary collapse
- Ideal to use in combination with mini cutter for cutting re-bar
- More silent than use of rescue saw: only pump produces sound



CC 23

VARIOUS RESCUE TOOLS

special materials cutter		SMC 5006	
art. no.		150.012.320	
blade opening	mm	25	
max. cutting force	kN / t	193 / 19.7	
cutting capacity ¹⁾	mm	Ø 20	
weight, ready for use	kg	6.5	

¹⁾ steel hardness 75 HRb



SMC 5006



A perfect combination: crushing concrete with the CC 23 and cutting re-bar with mini cutter CU 4007 C or SMC 5006

- Designed for heavy-duty work
- The crusher hardly generates any dust

pipe squeezer		HPS 60 AU	
art. no.		150.182.024	
max. squeezing force	kN / t	147 / 15	
max. outside ø pipe	mm	60	
max. wall thickness pipe	mm	4.0	
weight, ready for use	kg	8.6	



HPS 60 AU



cable cutters	steel cable			electric cable		
	HWC 16 R	HWC 25 R	HWC 32 R	HCC 85 R	HCC 100 R	
art. no.	150.012.266	150.012.267	150.012.268	150.012.269	150.012.270	
capacity	kN / t	52 / 5.3	146 / 14.9	249 / 25.4	49 / 5	87 / 8.9
max. jaw opening	mm	20	50	32	85	100
capacity steel cable 6 x 19	Ø mm	20	30	32	-	-
capacity solid steel	Ø mm	13	19	25	-	-
capacity ground cable	Ø mm	18	50	32	50	75
capacity telephone cable	Ø mm	-	-	-	85	100
weight, ready for use	kg	2.0	8.4	8.9	6.8	12.7



HWC 16 R



HWC 32 R



HCC 85 R

mini cutter HMC 8 U - single acting		Art. no.	
1	With fixed coupler		150.012.025
2	With 30 cm pigtail hose; in synthetic case		150.012.026
3	360° rotation elbow and 30 cm pigtail hose; in synthetic case		150.012.027
4	With 360° rotation elbow and handpump PA 04 H 2 S mounted with 2m. hose; in synthetic case		150.142.070
max. cutting force	kN / t	79 / 8.1	
depth / width of jaw	mm	40 / 40	
weight, ready for use	kg	3.0	



1



2



3



door openers		HDR 50 ¹⁾	HDO 100 ²⁾
art. no.		150.062.016	150.062.007
max. spreading force	kN / t	47 / 4.8	--
max. pushing force	kN / t	51 / 5.2	100 / 10.2
min. / max. width	mm	710 / 1310	-- / --
stroke	mm	--	130
weight, ready for use	kg	11.0	6.7

¹⁾ for pump (HTT 1250 ST) and hose, ask your local dealer

²⁾ with rotating hose connection and handle, delivered in synthetic carrying / storage box; also available with 30 cm pigtail hose, without handle (150.062.008)



HDR 50



HDO 100

