



Stanley GR29 Underwater Grinder

For grinding and cleaning underwater applications

The Stanley hydraulic GR29 grinder is a right angle grinder (“vertical grinder”) that can be used for grinding, cutting and cleaning in underwater applications with a variety of wheels, brushes and attachments.

Applications

Marine growth cleaning
Grinding & cutting

Features

Integral Stanley Hyrevz gear motor
Stainless steel spools and fasteners
Two position assist handle for right/
left hand operation
Oversized trigger with guard for
diver comfort
Adjustable wheel guard for infinite
positions
Plastisol covered handle for
comfortable ergonomic grip
Use with grinding wheels, hull
scrubbing brushes, wire and nylon
brushes, barnacle busters and
Desmond wheels
3200rpm @ 45lpm / 12gpm
Cast-in lifting eye

In the box

Stanley GR29 underwater grinder
ROV handle
Pin spanner
Operational hoses
Operations and maintenance manual



Stanley GR29 Underwater Grinder

Specifications



Capacity	230mm / 9in wheel
Spindle	5/8" - 11 threaded
Circuit type	Open center
Flow range	15-45lpm / 4-12gpm
Working pressure	70-140bar / 1000-2000psi
Full relief setting	155bar / 2250psi
RPM	3200rpm at 45lpm / 12gpm
Weight (with guard)	6.8kg / 15lbs
Length	280mm / 11in
Width (with guard)	260mm / 10.25in
Hydraulic ports	-8 SAE o-ring

Aberdeen
+44 (0)1224 771888

Abu Dhabi
+971 2 650 7710

Houston
+1 281 398 9533

Singapore
+65 6545 9350