

SIDEPAK™ PERSONAL AEROSOL MONITOR MODEL AM520i

The SidePak™ AM520i Personal Aerosol Monitors are small, portable, battery-operated, data-logging, light-scattering laser photometers that provide real-time aerosol mass concentration readings of dusts, fumes, mists, smoke and fog within a worker breathing zone. Newly designed inlet conditioners increase the mass concentration capability and provide size fraction cut points for PM₁₀, Respirable (PM₄), PM₅ (China Respirable), PM_{2.5}, PM₁ and 0.8µm Diesel Particulate Matter (DPM). This intrinsically safe monitor is the perfect solution for real-time, personal aerosol sampling in a variety of workplace environments, including but not limited to general industry, foundries, construction sites, chemical plants, refineries, petrochemical, power and utilities, transportation, aerospace, maritime, confined spaces and mining.



New Features

- + Robust impactors for higher mass concentration range
- + Audible and visual alarms
- + 0.8µm DPM impactor
- + High capacity "smart" battery
- + Color OLED display

Features and Benefits

- + Real-time mass concentration measurement and data logging for "in-the-field" data analysis
- + Push button menu operation or programmable through newly improved TrakPro™ v5 Data Analysis Software
- + User-selectable alarm levels to alert workers to high aerosol concentrations
- + Newly designed robust impactors enable reliable size fraction measurements at higher aerosol concentrations over longer run times
- + Model AM520i designed and tested to pass Intrinsic safety requirements as established by IEC (International Electrotechnical Commission) – see TSI App Note EXPMN-017 for a basic understanding of intrinsic safety

IECEX / ATEX

IECEX SIR 18.0043X
Sira 18ATEX2150X
IECEX SIM 19.0009X

Ex II 1G
Ex ia IIC T4 Ga
Ex ia I Ma
Rated: 12Vdc SELV
Ta = 0 °C to +50 °C



Intrinsic Safety Rating Information



Class 2258-03 Process Control Equipment –

Intrinsically Safe and Non-Incendive Systems -
For Hazardous Locations – Certified to Canadian Standards

- + Class I, Division I, Groups A, B, C, D,
- + Class II, Division I, Groups E, F, G,
- + Class III; T4; Ex ia IIC T4 Ga
- + Rated: 12VDC SELV, 3.0A
- + Ta = 0 °C to +50 °C


Class 2258-83 Process Control Equipment –

Intrinsically Safe and Non-Incendive Systems -
For Hazardous Locations – Certified to US Standards

- + Class I, Division I, Groups A, B, C, D; T4
- + Class I Zone 0 AEx ia IIC T4 Ga
- + Rated: 12VDC SELV, 3.0A
- + Ta = 0 °C to +50 °C



UNDERSTANDING, ACCELERATED



SPECIFICATIONS

SIDEPAK™ PERSONAL AEROSOL MONITOR MODEL AM520i

Sensitivity

Sensor Type 90° light scattering, 650 nm laser diode
Calibration Calibrated against a gravimetric reference using the respirable fraction of standard ISO 12103-1, A1 Test Dust

Aerosol Concentration Range 0.001 to 100 mg/m³
Particle Size Range 0.1 to 10 µm
Minimum Resolution 0.001 mg/m³
Zero Stability ±0.001 mg/m³ over 24 hours using 10 second time constant

Temperature Coefficient Approximately +0.0005 mg/m³ per °C (for variations from temperature at which instrument was last zeroed)

Flow Rate

Range User-adjustable, 0 to 1.8 liters/min (L/min) Note: Upper range is dependent on impactor or cyclone attached to the SidePak AM520/AM520i Monitor

Temperature Range

Operating Range 32° F to 120° F (0° C to 50° C)
Storage Range -4° F to 140° F (-20° C to 60° C)
Operational Humidity 0 to 95% RH, non-condensing

Time Constant (OLED Display)

Range User-adjustable, from 1 to 60 seconds

Built-in Inlets

Standard inlet Not size-specific
PM_{1.0} impactor 50% cut-off at 1.0 µm
PM_{2.5} impactor 50% cut-off at 2.5 µm
PM_{5.0} impactor 50% cut-off at 5.0 µm
PM₁₀ impactor 50% cut-off at 10.0 µm

Attachable Cyclones

4 µm Dorr-Oliver 50% cut-off at 4.0 µm
0.8 µm DPM 50% cut-off at 0.8 µm

Alarms

Alarm Types General, STEL
Default Settings 0.5 mg/m³, 1 mg/m³, 3 mg/m³, 5 mg/m³, 15 mg/m³, Off

Programmable from 0.001 to 999 mg/m³ through TrakPro Software

Alarm Indicator 95 dBA (at one foot) audible horn, blinking red LED, flashing red OLED display

Ringback Delay 30 sec, 1 min, 3 min, 5 min, 10 min, Off

Data Logging

Data Points Approx. 80,000 (55 days logging once per minute)

Logging Interval User-adjustable, from 1 second to 60 minutes

User-Select Calibration Factors

Factory Setting 1.0 (non-adjustable)
Ambient Setting 0.38 (non-adjustable)
User-Defined Settings 5, with user-defined labels via TrakPro Software
Range 0.1 to 10.0, user-adjustable

Physical

External Dimensions 5.1 x 3.7 x 3.1 inch
129.5 mm x 94 mm x 78.4 mm with 803322 battery
Weight 22 oz (0.62 kg) with 803322 battery
Display 160 x 128 resolution color OLED display
Tripod Mounting Nut ¼-20 female thread

Battery Pack (p/n 803322)

Rating 5100 mAh Li-Ion Pack
Run Time Greater than 20 hours at 1.7Lpm with a PM_{2.5} impactor
Charge Time 4.0 hours (typical with a fully depleted battery)

Power Supply (p/n 803302)

Input Voltage Range 100 to 240 VAC, 50 to 60 Hz
Output Voltage 12 VDC @ 3.0A

Maintenance

Factory Clean/Calibrate Recommended annually
User Zero Calibration Before each use
User Flow Calibration As needed with use of inlet conditioner

Communications Interface

Type USB 2.0
Connector, Instrument USB Micro-B (socket)

Minimum Computer Requirements for TrakPro Software

Communications Port Universal Serial Bus (USB) v2.0 or higher
Operating System Microsoft Windows® 7, 8, or 10 (32-bit or 64-bit) operating systems

Other Approvals

Model AM520i Battery Pack - P/N 803322



Immunity EN61326-1:2013
Emissions EN61326-1:2013 Class B
Safety IEC 61010-1:2010
IEC 60825-1:2014

Specifications are subject to change without notice.

TSI and the TSI logo are registered trademarks, and SidePak and TrakPro are trademarks of TSI Incorporated.

Microsoft and Windows are registered trademarks of Microsoft Corporation in the United States and/or other countries.



UNDERSTANDING, ACCELERATED

TSI Incorporated - Visit our website www.tsi.com for more information.

USA Tel: +1 800 874 2811
UK Tel: +44 149 4 459200
France Tel: +33 1 41 19 21 99
Germany Tel: +49 241 523030
India Tel: +91 80 67877200
China Tel: +86 10 8219 7688
Singapore Tel: +65 6595 6388



Tel: +44 (0)1462 679 020
london@ashtead-technology.com
www.ashtead-technology.com

Ashtead Technology Ltd
1 Gateshead Close
Sunderland Road
Sandy
Bedfordshire
SG19 1RS